

**IN THE CLAIMS:**

Please AMEND claims 47, 52, 54, and 78, as shown below.

1. (Original) A method of handling data packets in a network device, said method comprising:

receiving an incoming data packet;

parsing the incoming data packet to obtain a portion of the incoming data packet;

comparing said portion with rules stored in a rule table, where each rule of said rules specifies a set of actions;

selecting a match between said portion and a particular rule of said rules; and

executing a particular set of actions specified by said particular rule;

wherein each rule field of said rules includes a mask and a selection flag used in the comparing said portion with each rule.

2. (Original) A method of handling data packets as recited in claim 1, wherein the step of comparing said portion with rules stored in a rule table comprises comparing specific fields of the incoming data packet with corresponding rule fields in all of the rules stored in the rule table.

3. (Original) A method of handling data packets as recited in claim 2, wherein specific fields of the packet include a source port identification number and layer 2 to layer 7 headers.

4. (Original) A method of handling data packets as recited in claim 1, wherein the step of selecting a match between said portion and a particular rule of said rules comprises selecting a highest priority rule of said rules to be the particular rule when more than one rule of said rules match said portion.

5. (Original) A method of handling data packets as recited in claim 4, wherein the highest priority rule is determined by the addresses of said rules within said rules table.

6. (Original) A method of handling data packets as recited in claim 1, wherein said mask comprises an encoded compact mask and the step of comparing said portion with rules stored in a rule table comprises:

applying said encoded compact mask of said rule fields to corresponding fields of the incoming data packet to obtain a packet field value;

comparing the packet field value with a rule field value contained in said one of said rules; and

examining the selection flag of said one of said rule fields to determine whether said one of said rules is a potential match.

7. (Original) A method of handling data packets as recited in claim 6, wherein each rule has at least three types of rule fields comprising:

rule fields with a fixed location and a compact mask,

rule fields with a fixed field location and a full mask that is as wide as the packet field value, and

rule fields with a programmable field location which allows the rule field value to be mapped to any contiguous section of said portion of the incoming data packet.

8. (Original) A method of handling data packets as recited in claim 6, wherein the step of applying said mask of one of the rules comprises expanding the compact mask to a full mask as wide as the packet field value and applying the full mask to said portion.

9. (Original) A method of handling data packets as recited in claim 8, wherein the full mask is applied to said portion to obtain at least one of an IP destination address and an IP source address as the packet field value.

10. (Original) A method of handling data packets as recited in claim 7, further comprising the step of examining a global programmable flag to determine whether a start address of the programmable field location is a beginning of a layer 2 header or a layer 3 header of the incoming data packet.

11. (Original) A method of handling data packets as recited in claim 6, wherein the step of examining the selection flag comprises inverting the result of the comparing the packet field value step when the selection flag is set to a particular value.

12. (Original) A method of handling data packets as recited in claim 6, wherein the method further comprises determining a validity of the packet field value and using the determination to decide whether said one of said rules is the potential match.

13. (Original) A method of handling data packets as recited in claim 12, wherein the step of determining a validity of the packet field value comprises parsing said portion of the data packet to determine the validity and returning the validity result and the packet field value.

14. (Original) A method of handling data packets as recited in claim 12, wherein the step of determining a validity of the packet field value comprises comparing one or more programmable rule fields with certain packet field values in the incoming data packet, and, when the one or more programmable rule fields do not match, overriding comparison results of all other rule fields in the same rule.

15. (Original) A method of handling data packets as recited in claim 14, wherein the step of comparing one or more programmable rule fields with certain packet field values comprises determining how many bytes of the packet field value of the incoming data packet are present and indicating the rule field is not the match when mask bits of invalid bytes of the rule field value are not set to zeros.

16. (Original) A method of handling data packets as recited in claim 13, wherein the step of parsing said portion to determine validity further comprises determining whether a particular section of said portion required for a selected rule field value is present in the parsed portion.

17. (Original) A method of handling data packets as recited in claim 12, wherein the step of determining a validity of the packet field value comprises determining that one of said rules is the potential match when the packet field value is invalid but the compact mask of the rule field is all zeros.

18. (Original) A method of handling data packets as recited in claim 12, wherein the step of determining a validity of the packet field value comprises determining that one of said rules is the potential match when the packet field value is invalid but a valid bit of the rule field is set to zero.

19. (Original) A method of handling data packets as recited in claim 1, wherein the step of executing a particular set of actions specified by said particular rule comprises modifying a header of the incoming data packet, forwarding the incoming data packet to a destination address, or updating a management information register.

20. (Original) A method of handling data packets as recited in claim 19, wherein the step of updating a management information register comprises providing a bitmap used to increment individual counters indicating a forwarding, dropping, or processing of certain types of packets.

21. (Original) A method of handling data packets as recited in claim 19, wherein said particular set of actions comprises setting a flow identification for the incoming data packet such that the packet is classified according to a class of service.

22. (Original) A method of handling data packets as recited in claim 1, wherein the step of comparing said portion with rules stored in a rule table comprises comparing said portion with rules stored in a rule table implemented in a static random access memory, with three types of rule fields and action fields all stored in each row of the static random access memory.

23. (Original) A method of handling data packets as recited in claim 1, wherein the step of comparing said portion with rules stored in a rule table comprises comparing said portion with rules stored in a rule table implemented in a content addressed memory, where each entry of the content addressed memory includes a selection flag and a validity bit.

24. (Original) A network device for handling data packets comprising:

- a rules table;
- means for receiving an incoming data packet;
- means for parsing the incoming data packet to obtain a portion of the incoming data packet;
- means for comparing said portion with rules stored in said rule table, where each rule of said rules specifies a set of actions;
- means for selecting a match between said portion and a particular rule of said rules; and
- means for executing a particular set of actions specified by said particular rule;

wherein each rule field of said rules includes a mask and a selection flag used by the means for comparing said portion with each rule.

25. (Original) A network device for handling data packets as recited in claim 24, wherein the means for comparing said portion with rules stored in a rule table comprises

means for comparing specific fields of the incoming data packet with corresponding rule fields in all of the rules stored in the rule table.

26. (Original) A network device for handling data packets as recited in claim 25, wherein specific fields of the packet include a source port identification number and layer 2 to layer 7 headers.

27. (Original) A network device for handling data packets as recited in claim 24, wherein the means for selecting a match between said portion and a particular rule of said rules comprises means for selecting a highest priority rule of said rules to be the particular rule when more than one rule of said rules match said portion.

28. (Original) A network device for handling data packets as recited in claim 27, wherein the means for selecting a highest priority rule determines the highest priority rule by examining the addresses of said rules within said rules table.

29. (Original) A network device for handling data packets as recited in claim 24, wherein said mask comprises an encoded compact mask and the means for comparing said portion with rules stored in a rule table comprises:

means for applying said encoded compact mask of said rule fields to corresponding fields of the incoming data packet to obtain a packet field value;



means for comparing the packet field value with a rule field value contained in said one of said rules; and

means for examining the selection flag of said one of said rule fields to determine whether said one of said rules is a potential match.

30. (Original) A network device for handling data packets as recited in claim 29, wherein each rule has at least three types of rule fields comprising:

rule fields with a fixed location and a compact mask,

rule fields with a fixed field location and a full mask that is as wide as the packet field value, and

rule fields with a programmable field location which allows the rule field value to be mapped to any contiguous section of said portion of the incoming data packet.

31. (Original) A network device for handling data packets as recited in claim 29, wherein the means for applying said mask of one of the rules comprises means for expanding the compact mask to a full mask as wide as the packet field value and means for applying the full mask to said portion.

32. (Original) A network device for handling data packets as recited in claim 31, wherein the means for applying the full mask obtains at least one of an IP destination address and an IP source address as the packet field value.

33. (Original) A network device for handling data packets as recited in claim 30, further comprising means for examining a global programmable flag to determine whether a start address of the programmable field location is a beginning of a layer 2 header or a layer 3 header of the incoming data packet.

34. (Original) A network device for handling data packets as recited in claim 29, wherein the means for examining the selection flag comprises means for inverting the result of the means for comparing the packet field value, where the means for inverting inverts the result when the selection flag is set to a particular value.

35. (Original) A network device for handling data packets as recited in claim 29, wherein the network device further comprises means for determining a validity of the packet field value and decision means to decide whether said one of said rules is the potential match.

36. (Original) A network device for handling data packets as recited in claim 35, wherein the means for determining a validity of the packet field value comprises means for parsing said portion of the data packet to determine the validity and means for returning the validity result and the packet field value.

37. (Previously Presented) A network device for handling data packets as recited in claim 35, wherein the means for determining a validity of the packet field value comprises means for comparing one or more programmable rule fields with certain packet field values in the incoming data packet, and, means for overriding comparison results of all other rule fields in the same rule, where the means for overriding comparison results acts when the one or more programmable rule fields do not match.

38. (Original) A network device for handling data packets as recited in claim 37, wherein the means for comparing one or more programmable rule fields with certain packet field values comprises means for determining how many bytes of the packet field value of the incoming data packet are present and means for indicating the rule field is not the match when mask bits of invalid bytes of the rule field value are not set to zeros.

39. (Original) A network device for handling data packets as recited in claim 36, wherein the means for parsing said portion to determine validity further comprises means for determining whether a particular section of said portion required for a selected rule field value is present in the parsed portion.

40. (Original) A network device for handling data packets as recited in claim 35, wherein the means for determining a validity of the packet field value comprises means for determining that one of said rules is the potential match when the packet field value is invalid but the compact mask of the rule field is all zeros.

41. (Original) A network device for handling data packets as recited in claim 35, wherein the means for determining a validity of the packet field value comprises means for determining that one of said rules is the potential match when the packet field value is invalid but a valid bit of the rule field is set to zero.

42. (Original) A network device for handling data packets as recited in claim 24, wherein the means for executing a particular set of actions specified by said particular rule comprises means for modifying a header of the incoming data packet, means for forwarding the incoming data packet to a destination address, or means for updating a management information register.

43. (Original) A network device for handling data packets as recited in claim 42, wherein the means for updating a management information register comprises means for providing a bitmap used to increment individual counters indicating a forwarding, dropping, or processing of certain types of packets.

44. (Original) A network device for handling data packets as recited in claim 42, wherein the means for executing a particular set of actions comprises means for setting a flow identification for the incoming data packet such that the packet is classified according to a class of service.

45. (Original) A network device for handling data packets as recited in claim 24, wherein the rule table is implemented in a static random access memory, with three types of rule fields and action fields all stored in each row of the static random access memory.

46. (Original) A network device for handling data packets as recited in claim 24, wherein the rule table is implemented in a content addressed memory, where each entry of the content addressed memory includes a selection flag and a validity bit.

47. (Currently Amended) A computer program embodied on a computer readable medium encoding instructions for performing a ~~method~~process of handling data packets in a network device, wherein the computer program is configured to cause execution of the process when the instructions are executed, said ~~method~~process comprising:

receiving an incoming data packet;

parsing the incoming data packet to obtain a portion of the incoming data packet;

comparing said portion with rules stored in a rule table, where each rule of said rules specifies a set of actions;

selecting a match between said portion and a particular rule of said rules; and  
executing a particular set of actions specified by said particular rule;  
wherein each rule field of said rules includes a mask and a selection flag used in  
the comparing said portion with each rule.

48. (Previously Presented) The computer program of claim 47, wherein said  
mask comprises an encoded compact mask and the step of comparing said portion with  
rules stored in a rule table comprises:

applying said encoded compact mask of said rule fields to corresponding fields of  
the incoming data packet to obtain a packet field value;

comparing the packet field value with a rule field value contained in said one of  
said rules; and

examining the selection flag of said one of said rule fields to determine whether  
said one of said rules is a potential match.

49. (Previously Presented) The computer program of claim 48, wherein each rule  
has at least three types of rule fields comprising:

rule fields with a fixed location and a compact mask,

rule fields with a fixed field location and a full mask that is as wide as the packet  
field value, and

rule fields with a programmable field location which allows the rule field value to be mapped to any contiguous section of said portion of the incoming data packet.

50. (Previously Presented) The computer program of claim 48, wherein the step of applying said mask of one of the rules comprises expanding the compact mask to a full mask as wide as the packet field value and applying the full mask to said portion.

51. (Previously Presented) The computer program of claim 50, wherein the full mask is applied to said portion to obtain at least one of an IP destination address and an IP source address as the packet field value.

52. (Currently Amended) The computer program of claim ~~claim~~ 49, wherein the ~~method~~process further comprises examining a global programmable flag to determine whether a start address of the programmable field location is a beginning of a layer 2 header or a layer 3 header of the incoming data packet.

53. (Previously Presented) The computer program of claim 48, wherein the step of examining the selection flag comprises inverting the result of the comparing the packet field value step when the selection flag is set to a particular value.

54. (Currently Amended) The computer program of claim 48, wherein the ~~method~~process further comprises determining a validity of the packet field value and using the determination to decide whether said one of said rules is the potential match.

55. (Previously Presented) The computer program of claim 54, wherein the step of determining a validity of the packet field value comprises parsing said portion of the data packet to determine the validity and returning the validity result and the packet field value.

56. (Previously Presented) The computer program of claim 54, wherein the step of determining a validity of the packet field value comprises comparing one or more programmable rule fields with certain packet field values in the incoming data packet, and, when the one or more programmable rule fields do not match, overriding comparison results of all other rule fields in the same rule.

57. (Previously Presented) The computer program of claim 56, wherein the step of comparing one or more programmable rule fields with certain packet field values comprises determining how many bytes of the packet field value of the incoming data packet are present and indicating the rule field is not the match when mask bits of invalid bytes of the rule field value are not set to zeros.



58. (Previously Presented) The computer program of claim 55, wherein the step of parsing said portion to determine validity further comprises determining whether a particular section of said portion required for a selected rule field value is present in the parsed portion.

59. (Previously Presented) The computer program of claim 54, wherein the step of determining a validity of the packet field value comprises determining that one of said rules is the potential match when the packet field value is invalid but the compact mask of the rule field is all zeros.

60. (Previously Presented) The computer program of claim 54, wherein the step of determining a validity of the packet field value comprises determining that one of said rules is the potential match when the packet field value is invalid but a valid bit of the rule field is set to zero.

61. (Previously Presented) A network device for handling data packets, comprising:

a rules table;

a receiving unit configured to receive an incoming data packet;

a parsing unit configured to parse the incoming data packet to obtain a portion of the incoming data packet;

a comparing unit configured to compare said portion with rules stored in said rule table, where each rule of said rules specifies a set of actions;

a selecting unit configured to select a match between said portion and a particular rule of said rules; and

an executing unit configured to execute a particular set of actions specified by said particular rule;

wherein each rule field of said rules includes a mask and a selection flag used by the comparing unit in comparing said portion with said rule.

62. (Previously Presented) The network device of claim 61, wherein said mask comprises an encoded compact mask and the comparing unit comprises:

an applying unit configured to apply said encoded compact mask of said rule fields to corresponding fields of the incoming data packet to obtain a packet field value;

a comparison unit configured to compare the packet field value with a rule field value contained in said one of said rules; and

an examining unit configured to examine the selection flag of said one of said rule fields to determine whether said one of said rules is a potential match.

63. (Previously Presented) The network device of claim 62, wherein each rule has at least three types of rule fields comprising:

rule fields with a fixed location and a compact mask,

rule fields with a fixed field location and a full mask that is as wide as the packet field value, and

rule fields with a programmable field location which allows the rule field value to be mapped to any contiguous section of said portion of the incoming data packet.

64. (Previously Presented) The network device of claim 62, wherein the applying unit comprises an expanding unit configured to expand the compact mask to a full mask as wide as the packet field value and an application unit configured to apply the full mask to said portion.

65. (Previously Presented) The network device of claim 64, wherein the application unit is configured to obtain at least one of an IP destination address and an IP source address as the packet field value.

66. (Previously Presented) The network device of claim 63, further comprising:  
an examination unit configured to examine a global programmable flag to determine whether a start address of the programmable field location is a beginning of a layer 2 header or a layer 3 header of the incoming data packet.

67. (Previously Presented) The network device of claim 62, wherein the examining unit comprises an inverting unit configured to invert the result of the

comparison unit, where the inverting unit is configured to invert the result when the selection flag is set to a particular value.

68. (Previously Presented) The network device of claim 62, wherein the network device further comprises:

a determining unit configured to determine a validity of the packet field value; and  
a decision unit configured to decide whether said one of said rules is the potential match.

69. (Previously Presented) The network device of claim 68, wherein the determining unit comprises a parser unit configured to parse said portion of the data packet to determine the validity and a returning unit configured to return the validity result and the packet field value.

70. (Previously Presented) The network device of claim 68, wherein the determining unit comprises a comparer unit configured to compare one or more programmable rule fields with certain packet field values in the incoming data packet, and, an overriding unit configured to override comparison results of all other rule fields in the same rule, where the overriding unit is configured to act when the one or more programmable rule fields do not match.

71. (Previously Presented) The network device of claim 70, wherein the comparer unit comprises a determination unit configured to determine how many bytes of the packet field value of the incoming data packet are present and an indicating unit configured to indicate that the rule field is not the match when mask bits of invalid bytes of the rule field value are not set to zeros.

72. (Previously Presented) The network device of claim 69, wherein the parser unit further comprises a determination unit configured to determine whether a particular section of said portion required for a selected rule field value is present in the parsed portion.

73. (Previously Presented) The network device of claim 68, wherein the determining unit comprises a determination unit configured to determine that one of said rules is the potential match when the packet field value is invalid but the compact mask of the rule field is all zeros.

74. (Previously Presented) The network device of claim 68, wherein the determining unit comprises a determination unit configured to determine that one of said rules is the potential match when the packet field value is invalid but a valid bit of the rule field is set to zero.

75. (Previously Presented) A method of handling data packets in a network device, said method comprising:

comparing a portion of a received packet with rules stored in a rule table, where each rule of said rules specifies a set of actions;

selecting a match between said portion and a particular rule of said rules; and

executing a particular set of actions specified by said particular rule;

wherein each rule field of said rules includes a mask and a selection flag used in the comparing said portion with each rule.

76. (Previously Presented) A network device for handling data packets, comprising:

a rules table;

a comparing unit configured to compare a portion of a received packet with rules stored in said rule table, where each rule of said rules specifies a set of actions;

a selecting unit configured to select a match between said portion and a particular rule of said rules; and

an executing unit configured to execute a particular set of actions specified by said particular rule;

wherein each rule field of said rules includes a mask and a selection flag used by the comparing unit in comparing said portion with said rule.

77. (Previously Presented) A network device for handling data packets, comprising:

a rules table;

comparing means for comparing a portion of a received packet with rules stored in said rule table, where each rule of said rules specifies a set of actions;

selecting means for selecting a match between said portion and a particular rule of said rules; and

executing means for executing a particular set of actions specified by said particular rule;

wherein each rule field of said rules includes a mask and a selection flag used by the comparing means in comparing said portion with said rule.

78. (Currently Amended) A computer program embodied on a computer readable medium encoding instructions for performing a ~~method~~process of handling data packets in a network device, wherein the computer program is configured to cause execution of the process when the instructions are executed, said ~~method~~process comprising:

comparing a portion of a received packet with rules stored in a rule table, where each rule of said rules specifies a set of actions;

selecting a match between said portion and a particular rule of said rules; and

executing a particular set of actions specified by said particular rule;

wherein each rule field of said rules includes a mask and a selection flag used in the comparing said portion with each rule.